

## Mobile IPv6 Experimental Messages

### Status of This Memo

This document specifies an Internet standards track protocol for the Internet community, and requests discussion and suggestions for improvements. Please refer to the current edition of the "Internet Official Protocol Standards" (STD 1) for the standardization state and status of this protocol. Distribution of this memo is unlimited.

### Abstract

This document defines a new experimental Mobility Header message and a Mobility option that can be used for experimental extensions to the Mobile IPv6 protocol.

### Table of Contents

1. Introduction .....	1
2. Terminology .....	2
3. Experimental Mobility Header Message .....	3
4. Experimental Mobility Option .....	3
5. Security Considerations .....	4
6. IANA Considerations .....	5
7. Acknowledgements .....	5
8. References .....	5
8.1. Normative References .....	5
8.2. Informative References .....	5

### 1. Introduction

When experimenting with a protocol or defining a new extension to a protocol, one needs either a protocol number, a new message, or an option to carry the information related to the experiment. Most implementations end up using unassigned values for the new messages. Many times this creates problems when the same value is assigned through the IETF standards action, by IANA, or if the implementation gets deployed with these messages. Therefore, it is considered a good practice to set aside some code points that identify the experimental protocols or messages for experimental purposes. The need for experimental messages is shown in [3].

This document defines new messages for experimenting with extensions to the Mobile IPv6 protocol. These messages should be strictly used for experiments. Experiments that are successful should be standardized in the IETF. An implementation MUST NOT be released or deployed with the experimental messages.

This document defines a new Mobility Header message, which is the Experimental Mobility message that can be sent at any time by the mobile node, the home agent or the correspondent node. Since Mobility Header messages cannot be combined and sent in one packet, there is always only one Mobility Header message in any Mobile IPv6 packet. Home agent or correspondent node implementations that do not recognize the mobility message type, discard the message and send a Binding Error message as described in [2], with the Status field set to 2 (unrecognized MH Type value). Mobile nodes that do not recognize the mobility message type should discard the message and send an ICMP Parameter problem with code 0.

This document also defines a new mobility option, the Experimental Mobility option, which can be carried in any Mobility Header message. Mobility options, by definition, can be skipped if an implementation does not recognize the mobility option type [2].

The messages defined in this document can also be used for Network Mobility (NEMO) [4] and Proxy Mobile IPv6 [5] since these protocols also use Mobility Header messages.

Experimental code points could potentially disrupt a deployed network when experiments using these code points are performed in the network. Therefore, the network scope of support for experimental values should carefully be evaluated before deploying any experiment across extended network domains, such as the public Internet.

Experimental mechanisms should only be used for actual experimentation. By design, only a single code point is allocated for the message and another one for the option. This limits the number of experiments among a set of peers to one at a time. When experimental mechanisms are shown to be useful, and there is a desire to deploy them beyond the experiment they should be standardized and given new code points.

## 2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [1].



#### Type

An 8-bit field indicating that it is an experimental mobility option.

#### Length

An 8-bit field indicating the length of the option in octets excluding the Type and Length fields.

#### Data

Data related to the experimental protocol extension.

### 5. Security Considerations

Protection for the Experimental Mobility Header message and Mobility option depends on the experiment that is being carried out and the kind of information that is being carried in the messages. If these messages carry information that should not be revealed on the wire, or that can affect the binding cache entry at the home agent or the correspondent node, they should be protected in a manner similar to Binding Updates and Binding Acknowledgements.

Security analyzers such as firewalls and network intrusion detection monitors often rely on unambiguous interpretations of the fields described in this document. As new values for the fields are assigned, existing security analyzers that do not understand the new values may fail, resulting in either loss of connectivity, if the analyzer declines to forward the unrecognized traffic, or in loss of security if it does forward the traffic and the new values are used as part of an attack.

When experimental code points are deployed within an administratively self-contained network domain, it must be ensured that each code point is used consistently to avoid interference between experiments. When experimental code points are used in traffic that crosses multiple administrative domains, the experimenters should assume that there is a risk that the same code points will be used simultaneously by other experiments and that there is a possibility that the experiments will interfere. Particular attention should be given to security threats that such interference might create. Please see RFC 4727 for more details [6].

## 6. IANA Considerations

The Experimental Mobility Header message, defined in Section 3, has been assigned the type value (11), allocated from the same space as the 'MH Type' field in the Mobility Header [2].

The Experimental Mobility option, defined in Section 4, has been assigned the type value (18), allocated from the same space as Mobility Options [2].

## 7. Acknowledgements

The author would like to thank Jari Arkko and Basavaraj Patil with whom the contents of this document were discussed first.

## 8. References

### 8.1. Normative References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [2] Johnson, D., Perkins, C., and J. Arkko, "Mobility Support in IPv6", RFC 3775, June 2004.

### 8.2. Informative References

- [3] Narten, T., "Assigning Experimental and Testing Numbers Considered Useful", BCP 82, RFC 3692, January 2004.
- [4] Devarapalli, V., Wakikawa, R., Petrescu, A., and P. Thubert, "Network Mobility (NEMO) Basic Support Protocol", RFC 3963, January 2005.
- [5] Gundavelli, S., "Proxy Mobile IPv6", Work in Progress, March 2007.
- [6] Fenner, B., "Experimental Values In IPv4, IPv6, ICMPv4, ICMPv6, UDP, and TCP Headers", RFC 4727, November 2006.

Author's Address

Vijay Devarapalli  
Azair Networks  
4800 Great America Pkwy  
Santa Clara, CA 95054  
USA

EMail: [vijay.devarapalli@azairenet.com](mailto:vijay.devarapalli@azairenet.com)

## Full Copyright Statement

Copyright (C) The IETF Trust (2007).

This document is subject to the rights, licenses and restrictions contained in BCP 78, and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY, THE IETF TRUST AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in BCP 78 and BCP 79.

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

